



AIRCOL 266 & 299

Mineral Refrigeration Compressor Oil

Description

The Aircol 266 and 299 range of mineral based refrigeration oils is available as two grades of specially selected oils, highly refined, to provide chemical and thermal stability. Their low wax forming tendencies insure low pour points.

Application

Aircol 266 and 299 are specifically for use in refrigeration and air conditioning plants using fluorocarbon refrigerants. The exceptional low temperature characteristics of these oils prevent the flocculent precipitation of wax which can otherwise occur in high performance plant using Freon refrigerants.

In most systems using R22, the critical solution temperature characteristics of these oils are adequate to prevent oil/refrigerant separation problems within the low temperature circuits. Where evaporation temperatures are exceptionally low or in systems not incorporating oil/refrigerant separators, synthetic base refrigerant oils may be preferred.

Technical Data

Name	Method	Units	Aircol 266	Aircol 299
Density @ 15°C	ASTM D4052	g/ml	0.91	0.92
Viscosity @ 40°C	ASTM D445	cSt	32	55
Viscosity @ 100°C	ASTM D445	cSt	4.1	5.9
Closed Flash Point	ASTM D93	°C	165	183
Pour Point	ASTM D97	°C	-40	-36
Floc Point	DIN 51351	°C	-54	-48

Care and Handling

Avoid prolonged or repeated contact with skin. Wash thoroughly after handling.

Packaging and Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60C, exposed to hot sun or freezing conditions.

AIRCOL 266 & 299

12 Apr 2012

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Marine, Technology Centre, Whitchurch Hill, Pangbourne, Reading RG8 7QR, United Kingdom

www.castrolmarine.com