SAFETY DATA SHEET



Castrol Vecton Long Drain 10W-40

Section 1. Identifica	ation
GHS product identifier	Castrol Vecton Long Drain 10W-40
Product code	468266-MY01
SDS #	468266
Relevant identified uses of the	substance or mixture and uses advised against
Use of the substance/ mixture	Diesel engine oil. For specific application advice see appropriate Technical Data Sheet or consult our company representative.
Manufacturer	
Supplier	BP Philippines Inc. 30th floor LKG Tower 6801 Ayala Ave., Makati City 1226 Philippines
	Tel. No. (632) 884 1478 Fax. No. (632) 884 1911
EMERGENCY TELEPHONE NUMBER	Carechem: +65 3158 1203 (24 hours)
Section 2. Hazards	identification
GHS Classification	SKIN CORROSION/IRRITATION - Category 3 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A
GHS label elements	
Hazard pictograms	
Signal word	Warning
Hazard statements	H319 - Causes serious eye irritation. H316 - Causes mild skin irritation.
Precautionary statements	
Prevention	P280 - Wear eye or face protection. P264 - Wash hands thoroughly after handling.
Response	 P332 + P313 - If skin irritation occurs: Get medical attention. P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 - If eye irritation persists: Get medical attention.
Storage	Not applicable.
Storage Disposal	Not applicable. Not applicable.

Section 3. Composition/information on ingredients

Mixture

Substance/mixture

Chemically modified base oil Proprietary performance additives.

Product name Ca	astrol Vecton Long Drain 10W-40	Product	code 468266-N	/IY01 Page: 1/7
Version 1	Date of issue 30/09/2015.	Format GHS -	Philippines	Language ENGLISH
		Build 5.1.1 (GHS	- Philippines)	(ENGLISH)

Section 3. Composition/information on ingredients

Ingredient name	%	CAS number
Base oil - highly refined	≥75 - <90	Varies - See Key to abbreviations
Distillates (petroleum), hydrotreated, heavy paraffinic zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)	≥5 - <10 ≥1 - <2	64742-54-7 93819-94-4

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary firs	t aid measures
Inhalation	If inhaled, remove to fresh air. Get medical attention if symptoms occur.
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Get medical attention if adverse health effects persist or are severe.
Skin contact	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms occur.
Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Indication of immediate medical attention and special treatment needed, if necessary

Specific treatments	No specific treatment.
Notes to physician	Treatment should in general be symptomatic and directed to relieving any effects.

Section 5. Fire-fighting measures

Extinguishing media	
Suitable	In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.
Not suitable	Do not use water jet.
Specific hazards arising from the chemical	In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	Combustion products may include the following: phosphorus oxides metal oxide/oxides carbon oxides (CO, CO ₂) (carbon monoxide, carbon dioxide) sulfur oxides (SO, SO ₂ etc.)
Special precautions for fire- fighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

entering. Do not touch or walk through spilled material. Avoid breathing vapor mist. Provide adequate ventilation. Put on appropriate personal protective	personnel	equipment. Floors may be slippery; use care to avoid falling. Contact emergence
---	-----------	---

Product name Ca	astrol Vecton Long Drain 10W-40		Product code 468266-N	IY01 Page: 2/7
Version 1	Date of issue 30/09/2015.	Forma	at GHS - Philippines	Language ENGLISH
		Build 5.1.1	(GHS - Philippines)	(ENGLISH)

Section 6. Accidental release measures

For emergency responders	Entry into a confined space or poorly ventilated area contaminated with vapor, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for cont	ainment and cleaning up
Small spill	Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Contaminated absorbent material may pose the same hazard as the spilled product. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

Precautions for safe handling **Protective measures** Put on appropriate personal protective equipment (see Section 8). Avoid breathing vapor or mist. Avoid contact with eyes, skin and clothing. Do not ingest. Empty containers retain product residue and can be hazardous. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Do not reuse container. Advice on general Eating, drinking and smoking should be prohibited in areas where this material is occupational hygiene handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. Conditions for safe storage Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. Not suitable Prolonged exposure to elevated temperature.

Section 8. Exposure controls/personal protection

Control parameters

Ingredient name		Exposure limits
Base oil - highly refined		TLV (Philippines). TLV: 5 mg/m ³ 8 hours. Issued/Revised: 1/1978
Base oil - highly refined		TLV (Philippines). TLV: 5 mg/m ³ 8 hours. Issued/Revised: 1/1978
Recommended monitoring procedures	atmosphere or biological monitoring of the ventilation or other control me protective equipment. Reference sh	with exposure limits, personal, workplace may be required to determine the effectiveness assures and/or the necessity to use respiratory nould be made to appropriate monitoring uidance documents for methods for the ces will also be required.
Appropriate engineering controls	ensure exposures are adequately co only be considered after other forms have been suitably evaluated. Pers appropriate standards, be suitable for maintained. Your supplier of personal protective	evild be assessed for their risks to health, to ontrolled. Personal protective equipment should of control measures (e.g. engineering controls) onal protective equipment should conform to or use, be kept in good condition and properly equipment should be consulted for advice on . For further information contact your national
Product name Castrol Vecton Lor	g Drain 10W-40	Product code 468266-MY01 Page: 3/7
Version 1 Date of iss	ue 30/09/2015. Forma	at GHS - Philippines Language ENGLISH

Build 5.1.1

(GHS - Philippines)

(ENGLISH)

Section 8. Exposure controls/personal protection

	organisation for standards. Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye protection	Safety glasses with side shields.
Skin protection	
Hand protection	Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.
Skin protection	Use of protective clothing is good industrial practice. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Section 9. Physical and chemical properties

Appearance	
Physical state	Liquid.
Color	Brown.
Odor	Mild.
Odor threshold	Not available.
рН	Not available.
Melting point	Not available.
Boiling point	Not available.
Drop Point	Not available.
Flash point	Closed cup: 214°C (417.2°F) [Pensky-Martens.] Open cup: 232°C (449.6°F) [Cleveland.]
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable. Based on - Physical state
Lower and upper explosive (flammable) limits	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Product name Castrol Vecton Lo	ong Drain 10W-40 Product code 468266-MY01 Page: 4/7
Version 4 Data of is	aug 20/00/2015 Format CHS, Philippings I approach ENCLISH

 oduct name Castrol Vector Long Drain 10W-40
 Product code
 468266-MY01
 Page: 4/7

 Version 1
 Date of issue 30/09/2015.
 Format GHS - Philippines
 Language ENGLISH

 Build 5.1.1
 (GHS - Philippines)
 (ENGLISH)

Section 9. Physical and chemical properties

Density	866.7 kg/m³ (0.867 g/cm³) at 30°C
Solubility	insoluble in water.
Partition coefficient: n- octanol/water	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Kinematic: 88.24 mm²/s (88.24 cSt) at 40°C Kinematic: 13.54 mm²/s (13.54 cSt) at 100°C

Section 10. Stability and reactivity

Reactivity	No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.
Chemical stability	The product is stable.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerization will not occur.
Conditions to avoid	Avoid all possible sources of ignition (spark or flame).
Incompatible materials	Reactive or incompatible with the following materials: oxidizing materials.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicol	ogical effects			
Aspiration hazard				
Name		Result		
Distillates (petroleum)	, hydrotreated, heavy paraffinic	ASPIRATION HAZARD - Category 1		
Information on the like routes of exposure	Routes of entry anticipate	d: Dermal, Inhalation.		
Potential acute health	<u>effects</u>			
Eye contact	Causes serious eye irritat	ion.		
Inhalation	Vapor inhalation under ar vapor pressure.	mbient conditions is not normally a problem due to low		
Skin contact	Causes mild skin irritatior	 Defatting to the skin. 		
Ingestion	Irritating to mouth, throat	and stomach.		
Symptoms related to t	he physical, chemical and toxicolo	ogical characteristics		
Eye contact	Adverse symptoms may i pain or irritation watering redness	nclude the following:		
Inhalation	No specific data.			
Skin contact	Adverse symptoms may i irritation redness dryness cracking	nclude the following:		
Ingestion	No specific data.	No specific data.		
Delayed and immediat	e effects and also chronic effects	from short and long term exposure		
Inhalation	Overexposure to the inha of the respiratory tract.	lation of airborne droplets or aerosols may cause irritation		
Potential chronic hea	<u>Ilth effects</u>			
General	contaminate engine oils d components which have t contact with all types and	USED ENGINE OILS Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene maintained.		
Carcinogenicity	No known significant effe	cts or critical hazards.		
Mutagenicity	No known significant effe	cts or critical hazards.		
Product name Castrol \	/ecton Long Drain 10W-40	Product code 468266-MY01 Page: 5/7		
Version 1 D	ate of issue 30/09/2015.	Format GHS - Philippines Language ENGLISH		

Build 5.1.1

(GHS - Philippines)

(ENGLISH)

Section 11. Toxicological information

Teratogenicity Developmental effects Fertility effects No known significant effects or critical hazards. No known significant effects or critical hazards. No known significant effects or critical hazards.

Section 12. Ecological information

Environmental effects	No known significant effects or critical hazards.				
Persistence and degradability					
Not expected to be rapidly degradal	Not expected to be rapidly degradable.				
Bioaccumulative potential					
This product may bioaccumulate through food chains in the environment.					
Mobility	Spillages may penetrate the soil causing ground water contamination.				
Other adverse effects	No known significant effects or critical hazards.				
Other ecological information	Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.				
Section 12 Disposal considerations					

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	IMDG	IATA	
UN number	Not regulated.	Not regulated.	
UN proper shipping name	-	-	
Transport hazard class(es)	-	-	
Packing group	-	-	
Environmental hazards	No.	No.	
Additional information	-	-	

Special precautions for user Not available.

Transport in bulk according Not available. to Annex II of MARPOL 73/78 and the IBC Code

Product name Ca	astrol Vecton Long Drain 10W-40	Pro	oduct code	468266-MY01	Page: 6/7
Version 1	Date of issue 30/09/2015.	Format C	GHS - Philipp	oines L	anguage ENGLISH
		Build 5.1.1	GHS - Philip	pines)	(ENGLISH)

Section 15. Regulatory information

Regulation according to other	foreign laws
REACH Status	For the REACH status of this product please consult your company contact, as identified in Section 1.
United States inventory (TSCA 8b)	All components are listed or exempted.
Australia inventory (AICS)	All components are listed or exempted.
CANADA INVENTORY (DSL)	All components are listed or exempted.
China inventory (IECSC)	All components are listed or exempted.
Japan inventory (ENCS)	All components are listed or exempted.
Korea inventory (KECI)	All components are listed or exempted.
Philippines inventory (PICCS)	All components are listed or exempted.
Taiwan inventory (CSNN)	All components are listed or exempted.

Section 16. Other information

30/09/201	Б
30/09/201	Э.

revisionDate of previous issueNo previous validation.Prepared byProduct Stewardship

✓ Indicates information that has changed from previously issued version.

Notice to reader

Date of issue/Date of

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product name Ca	astrol Vecton Long Drain 10W-40		Product code 468266-M	MY01 Page: 7/7
Version 1	Date of issue 30/09/2015.	Format GHS - Philippines		Language ENGLISH
		Build 5.1.1	(GHS - Philippines)	(ENGLISH)